



PCB HOLES(TOP VIEW)
GENERAL TOLERANCE:±0.05mm

- NOTES:
- ELECTRICAL CHARACTERISTICS:
 - RATING: DC 24V 0.5A;
 - CONTACT RESISTANCE:≤30mΩ;
 - INSULATION RESISTANCE:≥500MΩ DC 500V;
 - WITHSTANDING VOLTAGE:AC 500V 1min;
 - LIFE:500 CYCLES;
 - MECHANICAL CHARACTERISTICS:
 - INSERTION&EXTRACTION FORCE:3~30N;
 - OPERATING TEMPERATURE:-25°C~+70°C;

NO.	PART NAME	QTY	MATERIAL	PLATING	REMARK
4	PIN	1	COPPER ALLOY	Tin plating	T=0.3
3	FRAME	1	Electrolytic timplate	-	T=0.3
2	HOUSING	1	PPA	-	BROWN
1	IEC socket	1	Iron	Matte tin	

浙江富港电子有限公司

TOLERANCE UNLESS OTHERWISE SPEC	TOLERANCE
BASIC DIMENSION	±0.50
x.x	±0.30
x.xx	±0.10
x.xxx	±3°
ANGLES	±3°

DSND	W Z Z	TITLE:IF	RF socket
CHKD	L P J	PART NO:IF-3520TM-5.0	
APVD	L Z W		
UNIT:mm	SCALE:1:1	SIZE:A4	SHEET:1/1