



技术特性:

- 使用条件: -30~70°
- 额定负荷: DC30V 1A
- 接触电阻: ≤0.02 Ω
- 绝缘电阻: ≥100MΩ DC250V
- 耐压: AC250V(50Hz) 1min
- 插拔力: 3~15N
- 寿命: 5000次

PCB LAYOUT
TOP VIEW (TOLERANCE:±0.05)

SCHMATIC

6	盖板	1	PA66	黄
5	插针	1	H59黄铜棒	铜镍
4	平片	1	H62黄铜带(Y) δ=0.30mm	铜镍
3	弯片	1	H62黄铜带(Y) δ=0.30mm	铜镍
2	弹片	1	65Mn 锰钢带 δ=0.20mm	铜镍
1	底座	1	PA66	黑
序号	名称	数量	材料	备注

GENERAL TOLERANCES			
0.X	±0.30	X°	±3°
0.XX	±0.20		
0.XXX	±0.10	X.X°	±1°
UNIT	SIZE	SCALE	
MM	A4	1:1	

DRAWN		C	TITLE: 电源插座
DESIGN		PART NO.	DC-015-2.0-MN
CHECKED		PRODUCT NO.	
APPROVED		DRAWING NO.	
		UNIT: mm	SCALE: 1:1 REV:01-1 SHT:10F1

浙江创都电子科技有限公司

ECN NO.	REV	DATE	DESCRIPTION	MDF'D	APP'D
	01	2021.12.22	NEW DRAWING RELEASE		