



| | | |
|------------|----------------------|------------|
| 目录 MAPX | 设变内容 MODIFICATION | 日期 DATE |
| | | |

规格说明: Specifications:

电气特性: Electrical:

1. 额定电流: Current Rating
1A/contact terminalg
2. 额定电压: Voltage Rating
30V DC
3. 接触阻抗: Contact Resistance
30 milliohms MAX
4. 耐电压: Dielectnic Withstanding
Voltage

500 V AC AT Sea Level

5. 绝缘阻抗: Insulation Resistance
1000MEGA ohms MIN

物理性能: Mechanical:

1. 插拔力: Cnector Mate and Unmate Force
Mate force: 35N (MAX)
Unmate force: 7N (MIN)

材料: Matorial:

1. 塑胶: Housing:
PBT
2. 端子: Contact:
Copper Alloy C2680
3. 外壳: Shell:
SPCC

电镀Finish:

1. 端子: Contact:
Plated Gold in Mating Area,
Tin On Solder Tails
2. 外壳: Shell
Nickel Plating

温度范围: Temperature Range:
-30 C to +80 C

| | | | | | | | | | | |
|--|-------|-----|-----|--------------------|------------|---------------|-----|--------------------------|---------------------|----|
| 产品图 PRODUCT CHART DWG | | | | 深圳市韩下电子有限公司 | | | | | | |
| 公差表 TOLERANCE UNLESS OTHERWISE | | | | 单位 UNITS | MM | 制图 DRAWING | 黄彬 | 客户料号 PRODUCT PART NO. | | |
| X. | ±0.30 | X' | ±6' | 比例 SCALE | 1:1 | 审核 CHKD | 张伟 | 产品名称 PRODUCT NO. | HX AF 10.0 QTZB 6.3 | |
| .X | ±0.25 | .X' | ±3 | 日期 DATE | 2014/04/23 | 核准 APPD | 罗小春 | 角法 VIEW | 版本 VER | A0 |
| 未标注的公差按一般标准计算 | | | | | | | | | | |