

1		2			3			4		5		6		7		8	
linear dimension(Tolerances Standard GB/T 14486-2008)								—	\square	\perp	版本 Version	描述 Description	设计 Design	批准 Approved	日期 Date		
A	variable range	to	over	over	over	over	over	to	over	over	A	新发行	熊武敌	楼特高	2024.03.10		
	6	6	10	10	30	30	60	10	100	100							
tolerance		± 0.20	± 0.30	± 0.50	± 0.70	± 1.00	± 1.30	± 1.60	0.10	0.30	0.60						
B												材质及电镀 MATERIAL 螺丝 Screws: M2.5, 钢, 镀锌 夹片 Clamp: 铜合金, 镀镍 方块 Cage: 铜合金, 镀镍 塑件 Housing: PA66, UL94V-0					
C												电气性能 ELECTRICAL 参考标准 Stanard: UL IEC 额定电压 Rated voltage: 300V 320V 额定电流 Rated current: 10A 15A 使用线径 Wire range: 24-12AWG 2.5mm ² 接触电阻 Contact resistance: 20mΩ 绝缘电阻 Insulation resistance: 500MΩ/DC500V 耐电压 Withstanding voltage: AC1600V/1Min					
D												机械性能 MECHANICAL 温度范围 Temp. range: -40℃ ~ +105℃ 瞬时温度 Max. soldering: +250℃ for 5 Sec 扭矩 Torque: 4.08kgf.cm/0.4N.m 剥线长度 Strip length: 7~8mm					
E												编码原则(Product Number Code): WJ2EDGKM-5.08-XXP-1Y-00A 产品型号(Series No.) 间距(Pitch) 极数(No. of Poles) 客户需求(Customer Request) 塑体颜色(Housing Color)					
F												1: 单倍间距 (Single Pitch) 2: 双倍间距 (Double Pitch) 1: 灰色(Grey) 6: 红色(Red) 2: 蓝色(Blue) 7: 透明(Transparent) 3: 黑色(Black) 8: 黄色(Yellow) 4: 绿色(Green) 9: 白色(White) 5: 橙色(Orange)					
G												插拔式接线端子 PLUG-IN TERMINAL BLOCK					
H	第三视角 (THIRD ANGLE PROJECTION) 图纸类型 (TYPE) CUSTOMER DRAWING 单位 (UNITS) mm 尺寸 (SIZE) A4 比例 (SCALE) 1:1 图页 (SHEET) 1/1											型号 (NAME) WJ2EDGKM-5.08-XXP-1Y-00A 版本 (VERSION) A 宁波康奈克斯电气有限公司 NINGBO KANGNEX ELECTRIC., LTD.					