



适应基板厚度: 1.2mm—1.6mm
 温度范围: -25C° —85C°
 额定电压: 250V AC/DC
 额定电流: 2A
 接触电阻: ≤0.01Ω
 绝缘电阻: ≥1000MΩ
 耐压: 800V AC/minute

型号 Type	尺寸Dimensions mm	
	A	B
2P	6.0	2.0
3P	8.0	4.0
4P	10.0	6.0
5P	12.0	8.0
6P	14.0	10.0
7P	16.0	12.0
8P	18.0	14.0
9P	20.0	16.0
10P	22.0	18.0
11P	24.0	20.0
12P	26.0	22.0
13P	28.0	24.0
14P	30.0	26.0
15P	32.0	28.0

技术要求:

- 1) 材质: 见附表.
- 2) 电镀: 见附表.
- 3) 塑件表面平整、光洁、无毛刺、气泡、烧焦、变形、浇口无拉伤、多料或缺料等不良现象.
- 4) 端子表面无氧化、电镀不良等现象.

2	PIN	材质: 黄铜, 电镀: 亮锡60u"MIN	一般公差 TOLERANCES X. ±0.15 .XX±0.05 .X±0.1 .XXX±0.02 ABCDES±1°	连兴旺电子(深圳)有限公司 LXWCONN ELECTRONICS (SHENZHEN) CO., LTD
1	Housing	材质: PA66 (UL94V-0), 颜色: 本色		
NO.	Draw Name	PH-XXAW	审核 批准 时间 2021.06.08	时间 2021.06.08
A	B	C	D	F