



适应基板厚度: 1.2mm—1.6mm
 温度范围: -25°C —85°C
 额定电压: 250V AC/DC
 额定电流: 3A
 接触电阻: ≤0.01Ω
 绝缘电阻: ≥1000MΩ
 耐压: 1000V AC/minute

型号 Type	尺寸Dimensions mm	
	A	
2P	7.5	
3P	10	
4P	12.5	
5P	15	
6P	17.5	
7P	20	
8P	22.5	
9P	25	
10P	27.5	
11P	30	
12P	32.5	
13P	35	
14P	37.5	
15P	40	

技术要求:

- 1) 材质: 见附表.
- 2) 电镀: 见附表.
- 3) 塑件表面平整、光洁、无毛刺、气泡、烧焦、变形、浇口无拉伤、多料或缺料等不良现象.
- 4) 端子表面无氧化、电镀不良等现象.

2	PIN	材质: 黄铜, 电镀: 亮锡60u"MIN	一般公差 TOLERANCES X. ±0.15 .XX±0.05 .X±0.1 .XXX±0.02 ABGRES±1°	连兴旺电子(深圳)有限公司 LXWCONN ELECTRONICS (SHENZHEN) CO., LTD	品名: 2.5XH卧式	制图
1	Housing	材质: PA66 (UL94V-0), 颜色: 本色			材料: PA66	审核
NO.	Draw Name	XH-XXAW	比例: 1:1	单位: mm	时间: 2021.06.08	